

NOTICE TO BIDDERS
ROLL-OFF CONTAINER TRUCK WITH HOIST

Notice is hereby given that the Board of County Commissioners of Santa Rosa County, Florida, will receive sealed bids for a **Roll-off Container Truck with Hoist**.

All bids must be original and delivered by hand, Fed Ex, or mail to the Santa Rosa County Procurement Department, 6495 Caroline Street, Suite G, Milton, Florida, 32570; and must be received by 10:00 a.m., November 18, 2008, at which time bids will be opened and read aloud. Bids received after the time set for the bid opening will be rejected and returned unopened to the bidder. All interested parties are invited to attend.

Specifications and bid form may be secured from Santa Rosa County Website (www.santarosa.fl.gov/bids), or at the Santa Rosa County Procurement Department at the above address. Telephone (850) 983-1870.

Any questions concerning this equipment should be directed to Jerrel Anderson at (850) 626-0191.

The Board of County Commissioners reserves the right to waive irregularities in bids, to reject any or all bids with or without cause, and to award the bid that it determines to be in the best interest of Santa Rosa County.

Santa Rosa County does not discriminate on the basis of race, color, national origin, sex, religion, age, or handicapped status in employment or provision of service.

By order of the Board of County Commissioners of Santa Rosa County, Florida.

LEGAL NOTICE

One issue – October 18, 2008 - Press Gazette, October 23, 2008 –Navarre Press

Bill and proof to Santa Rosa County Procurement Department, 6495 Caroline Street, Suite G, Milton, Florida, 32570, Attn.: Orrin L. Smith.

October 18, 2008

MEMORANDUM

TO: Company Addressed

FROM: Santa Rosa County Procurement Department

SUBJECT: Roll-Off Container Truck with Hoist

Notice is hereby given that the Board of County Commissioners of Santa Rosa County, Florida, will receive sealed bids for a Roll-off Container Truck with Hoist.

All bids must be original and delivered by hand, Fed Ex, or mail to the Santa Rosa County Procurement Department, 6495 Caroline Street, Suite G, Milton, Florida, 32570; and must be received by 10:00 a.m., November 18, 2008, at which time bids will be opened and read aloud. All interested parties are invited to attend.

Bids are to be sealed and plainly labeled “**BID – ROLL-OFF CONTAINER TRUCK WITH HOIST**”, Bids received after the time set for the bid opening will be rejected and returned unopened to the bidder.

Specifications and bid form may be secured from Santa Rosa County Website (www.santarosa.fl.gov/bids), or at the Santa Rosa County Procurement Department at the above address. Telephone (850) 983-1870.

Any questions concerning this equipment should be directed to Jerrel Anderson at (850) 626-0191.

The Board of County Commissioners reserves the right to waive irregularities in bids, to reject any or all bids with or without cause, and to award the bid that it determines to be in the best interest of Santa Rosa County.

Santa Rosa County does not discriminate on the basis of race, color, national origin, sex, religion, age, or handicapped status in employment or provision of service.

ROLLOFF TRUCK WITH HOIST MINIMUM SPECIFICATIONS

INTENT:

This specification describes the minimum requirements to furnish a truck chassis with Roll-Off Hoist with the following minimum specifications. The hoist shall be capable of lifting and transporting 20' - 22' Roll-Off containers (outside rail) and capable of dispensing the load by means of hydraulically dumping the load from these containers. The manufacturer shall have produced this refuse collection equipment for a period of at least ten (10) years.

GENERAL TERMS:

All equipment furnished under this contract shall be new, unused and the same as the manufacturer's current production model. Accessories not specifically mentioned herein, but necessary to furnish complete unit ready for use, shall also be included. Unit shall conform to the best practice known to the body trade in design, quality of material and workmanship. Assemblies, sub-assemblies and component parts shall be standard and interchangeable throughout the entire quantity of units as specified in this invitation to bid. The equipment furnished shall conform to ANSI Safety Standard Z245.1-1992.

GUARANTEE:

Bidder shall state his normal warranty and extended warranty where available.

PARTS MANUAL:

Bidder shall furnish complete parts, maintenance, and operator's manuals with each body sold. A parts manual must be furnished for truck and engine parts as well as hoist frame. A shop tech manual should also be furnished for truck, engine and hoist frame.

Bidder shall complete every space in the specification bidders proposal column with a check mark to indicate if the item being bid is exactly as specified. If not, the "NO" column must be checked and a detailed description of the deviation from the specification to be supplied.

I. ROLL-OFF HOIST

Manufacturer's Rated Capacity: 60,000 Pounds.	<input type="checkbox"/>	<input type="checkbox"/>	_____
Recommended Container Lengths: 20 - 22 Feet	<input type="checkbox"/>	<input type="checkbox"/>	_____
Working Hydraulic Pressure: 1850 PSI	<input type="checkbox"/>	<input type="checkbox"/>	_____
Approximate Operating Times:			
Hoist Up > 30 seconds	<input type="checkbox"/>	<input type="checkbox"/>	_____
Hoist Down > 15 seconds	<input type="checkbox"/>	<input type="checkbox"/>	_____
Container On > 46 seconds	<input type="checkbox"/>	<input type="checkbox"/>	_____
Container Off > 37 seconds	<input type="checkbox"/>	<input type="checkbox"/>	_____
Raised Dump Angle: minimum 48 degrees	<input type="checkbox"/>	<input type="checkbox"/>	_____
Main Frame: 8" x 4" x 1/2" (ASTM A-500 / Grade-C) Rectangular Tubing.	<input type="checkbox"/>	<input type="checkbox"/>	_____
Sub Frame: 3" x 2" x 3/16" (ASTM A-500) Rectangular Tubing.	<input type="checkbox"/>	<input type="checkbox"/>	_____
Cable: 7/8" Diameter X 71' Length, 6X37 EX1WRC Regular Right Lay	<input type="checkbox"/>	<input type="checkbox"/>	_____
Cable End: Cast Steel Swivel Cable Eye Tested To 78,000 Pounds. Cable Opening To Be Approximately 5-3/8" Long X 1-3/4" Wide. Overall Length Of The Eye Shall Be 12" With A Width Of 3-5/8".	<input type="checkbox"/>	<input type="checkbox"/>	_____
Cable Capacity Rating: 39 Tons.	<input type="checkbox"/>	<input type="checkbox"/>	_____
Cable Sheave Shafts: 2.5" Diameter Inch Hardened Steel Equipped With Grease Zerks.	<input type="checkbox"/>	<input type="checkbox"/>	_____
Cable Sheave Guides: 4" Channel Steel	<input type="checkbox"/>	<input type="checkbox"/>	_____
Side Rollers: Five (5) Per Side. (4" O.D. X 2" I.D.) Rollers Are To Be Equipped With Bronze Bushed Bearings.	<input type="checkbox"/>	<input type="checkbox"/>	_____
Side Roller Shafts: 2" Diameter Hardened Steel Shafts Supported By 1/2" X 3" X 5" Base Plated Welded To Main Frame Rail. The Roller Shaft Is To Be Machined And Fitted With Grease Zerks For Routine Lubrication.	<input type="checkbox"/>	<input type="checkbox"/>	_____
Rear Ground Roller: 6-5/8" O.D. X 23" Width.	<input type="checkbox"/>	<input type="checkbox"/>	_____
The Forward End Of The Hoist Frame Structure Shall Be Equipped With One (1) Vertical 10" O.D. Cast Bronze Bushed Sheave. The Sheave Shall Rotate On A Heat-Treated Steel Pin Of Not Less Than 2" O.D. With Grease Zerk Provided For Routine Lubrication.	<input type="checkbox"/>	<input type="checkbox"/>	_____
The Hoist Frame Shall Include Forward Container Radius Stops Constructed Of 1-1/2" Steel Plate. Stops Are To Provide An Automatic Locking Device Actuated When The Container Is Loaded In The Full Forward Position And The Hoist Is In The Fully Lowered Position.	<input type="checkbox"/>	<input type="checkbox"/>	_____

The Hoist Frame Shall Provide Two (2) D.O.T. And I.C.C. Container Safety Hold Down Locks At The Rear And Midframe Of The Hoist.	<input type="checkbox"/>	<input type="checkbox"/>	_____
Rear Hinge Assembly: Four 1-1/4" Thick Rear Hinge Plates Welded To The Hoist Sub Frame	<input type="checkbox"/>	<input type="checkbox"/>	_____
Hinge Pins: 1-15/16" O.D. Heat Treated Steel With Grease Zerks For Routine Lubrication	<input type="checkbox"/>	<input type="checkbox"/>	_____
Lower Lift Cylinder Mounting Shaft: 2-1/2" O.D. Steel	<input type="checkbox"/>	<input type="checkbox"/>	_____
Lift Cylinders: Two (2) Double Acting 6" Diameter With 72" Stroke	<input type="checkbox"/>	<input type="checkbox"/>	_____
Reeving Winch Cylinders: Two (2) Double Acting 7" Diameter With 80" Stroke Inboard Mounted Between The Hoist Frame Rails.	<input type="checkbox"/>	<input type="checkbox"/>	_____
Reeving Winch Cylinder Protection: Cylinder Rods Are To Be Protected By 3/8" X 3" Steel Flat Bar Welded Between The Hoist Main Frame	<input type="checkbox"/>	<input type="checkbox"/>	_____
Safety Props: Hoist Frame Shall Include Two (2) Safety Maintenance Props; One On Each Side Of The Hoist Rail	<input type="checkbox"/>	<input type="checkbox"/>	_____
Rear Bumper: Bumper Installed Across The Rear. The Bumper Shall Provide An I.C.C. Regulation Folding Safety Bumper.	<input type="checkbox"/>	<input type="checkbox"/>	_____
Lights & Reflectors: The Rear Bumper Shall Be Equipped With A Center Mount I.C.C. 3-Light Red Running Lights, Two (2) Corner Clearance Lights, Four (4) Brake & Directional Lights, And Two (2) Reverse Lights.	<input type="checkbox"/>	<input type="checkbox"/>	_____
Hydraulic PTO: Direct / Close Coupled Air Shift PTO	<input type="checkbox"/>	<input type="checkbox"/>	_____
Hydraulic Pump: Direct / Close Coupled Gear Type, 35 GPM @ 1500 RPM Output Rating And To Operate At 1850 PSI.	<input type="checkbox"/>	<input type="checkbox"/>	_____
Control Valve: 2-Spool, 45 GPM With Safety Bypass System	<input type="checkbox"/>	<input type="checkbox"/>	_____
Controls: Air-Type Controls For The Valve Shall Be Located Inside The Cab To The Drivers Right With A Duplicate Set Of Controls Supplied On The Street-Side Adjacent To The Driver's Door. Controls To Be Of The Air Valve Design.	<input type="checkbox"/>	<input type="checkbox"/>	_____
Filter: 25 Micron Replaceable Design	<input type="checkbox"/>	<input type="checkbox"/>	_____
Oil Reservoir: 50-Gallon Capacity Equipped With A Breather Cap, Level Sight Gauge, and Temperature Gauge.	<input type="checkbox"/>	<input type="checkbox"/>	_____
Shut Off Valve: A 1-1/4" Gate Type Shut Off Valve Shall Be Provided.	<input type="checkbox"/>	<input type="checkbox"/>	_____
Hydraulic Hose: Hydraulic Lines Shall Be Shielded With Nylon Protective Sleeve Material Where Abrasion Possibilities Exist. Hydraulic Lines Routed In Close Proximity To The Operating Reeving Cables Shall Be Metal Wrapped For Protection.	<input type="checkbox"/>	<input type="checkbox"/>	_____
Fenders: Heavy Duty Steel Fenders Are To Be Installed Over The Rear Tires.	<input type="checkbox"/>	<input type="checkbox"/>	_____
Storage: 20" x 16" x 48" Toolbox	<input type="checkbox"/>	<input type="checkbox"/>	_____

Paint: Hoist Shall Have A Black Primer Base Coat And Then Be Painted In Flat Black Enamel Paint.

II. CHASSIS

ENGINE

Minimum inline 6 cylinder diesel, 275 horsepower, 800ft/lbs torque.

Engine Mounted Oil Check & Fill

Dual Air Intake Through LH & RH Sides With Donaldson Air Cleaner, Firewall Mounted

DR 12V130 AMP 22-SI Quadramount PAD Alternator

Two (2) Alliance 1131 GRP31 12V MF 1900 CCA Threaded Stud Batteries

Battery Shutoff Switch at Battery Box

BW 15.9 CFM Model BA-921 Single Cylinder Compressor

Single horizontal Muffler, With Horizontal Tail Pipe Exhaust, Right Hand Mounted

Borg Warner Viscous Fan Drive

Spin-on Fuel Filter

Fuel Line Primer Pump

Full Flow Oil Filter

1000 Sq-In Radiator – Aluminum

Air Intake Warmer

Delco 12V 38MR HD Starter or equivalent.

TRANSMISSION

Minimum Allison 3560 Automatic Transmission

FRONT AXLE & SUSPENSION

Meritor MFS-18-133A Front Axle @ 18,000lbs or equivalent

Meritor 16.5 x 6 Q+ Cast Front Brakes or equivalent

Chicago Rawhide Scotseal Front Oil Seals or equivalent

Meritor Automatic Front Slack Adjusters or equivalent

TrwTHP-60 Power Steering or equivalent

Minimum 18,000lb Flat Leaf Front Suspension

Graphite Bronze Bushings with Seals – Front Suspension or equivalent

Front Shock Absorbers

REAR AXLE & SUSPENSION

Meritor RT-44-145 R-Series Tandem Rear Axle @ 44,000lbs or equivalent

18N Meritor Main Driveline with Full Round Yokes or equivalent

17N Meritor Interaxle Driveline with Full Round Yokes or equivalent

Interaxle and/or Differential Lockout with Indicator Light or equivalent

Meritor 16.5 x 7 Q+ Cast Rear Brakes or equivalent

Chicago Rawhide Scotseal Rear Oil Seals or equivalent

Meritor Automatic Rear Slack Adjusters or equivalent

Hendrickson RT463 Rear Suspension @ 46,000lbs or equivalent

54" Axles Spacing

Steel Beams & Bronze Center Bushings with Bar Pin Adjustable End

Connection Fore/Aft Control Rods

BRAKE SYSTEM

Wabco 4S/4M ABS Without Traction Control Enhancement or equivalent

BW AD-9 Brake Line Air Dryer With Heater or equivalent

Drain Valves on All Air Tanks

FRAME & WHEELBASE

Minimum 254" Wheelbase

Minimum 11/32" x 3-1/2" x 10-15/16" Steel Frame (8.73MM X 277.8/.344" X

Minimum 10.94") 120,000 psi	<input type="checkbox"/>	<input type="checkbox"/>	_____
Minimum 1/4" (6mm) C-Channel Inner Frame	<input type="checkbox"/>	<input type="checkbox"/>	_____
63" Overhang	<input type="checkbox"/>	<input type="checkbox"/>	_____

CHASSIS EQUIPMENT

12" Painted Steel Straight Bumper	<input type="checkbox"/>	<input type="checkbox"/>	_____
Grade 8 Threaded Hex-Headed Frame	<input type="checkbox"/>	<input type="checkbox"/>	_____
Front Tow Hooks – Frame Mounted	<input type="checkbox"/>	<input type="checkbox"/>	_____

FUEL TANKS & EQUIPMENT

Minimum 90 Gallon Aluminum Fuel Tank	<input type="checkbox"/>	<input type="checkbox"/>	_____
Alliance Fuel/Water Separator with Indicator Light	<input type="checkbox"/>	<input type="checkbox"/>	_____

FRONT TIRES

Radial-385/65R 22.5 18 Ply	<input type="checkbox"/>	<input type="checkbox"/>	_____
----------------------------	--------------------------	--------------------------	-------

REAR TIRES

Radial-H/T 11R 22.5 14 Ply	<input type="checkbox"/>	<input type="checkbox"/>	_____
----------------------------	--------------------------	--------------------------	-------

CAB EXTERIOR

101" BBC Conventional Steel Cab or equivalent	<input type="checkbox"/>	<input type="checkbox"/>	_____
Rubber Cab Mounts	<input type="checkbox"/>	<input type="checkbox"/>	_____
5" Fender Extensions	<input type="checkbox"/>	<input type="checkbox"/>	_____
Grabhandles LH/RH	<input type="checkbox"/>	<input type="checkbox"/>	_____
Dual Round Air Horns, Single Base, Cab Roof Mounted	<input type="checkbox"/>	<input type="checkbox"/>	_____
Single Electric Horn	<input type="checkbox"/>	<input type="checkbox"/>	_____
Dual SST West Coast Mirrors (door mounted)	<input type="checkbox"/>	<input type="checkbox"/>	_____
LH/RH 8" Convex Mirrors, Mounted Under Primary Mirrors	<input type="checkbox"/>	<input type="checkbox"/>	_____
Factory Tinted glass, all windows	<input type="checkbox"/>	<input type="checkbox"/>	_____

CAB INTERIOR

Heater, Defroster, and Air Conditioner	<input type="checkbox"/>	<input type="checkbox"/>	_____
Bostrom 915 High Back Talladega Driver's Seat or equivalent	<input type="checkbox"/>	<input type="checkbox"/>	_____
EZYRider Mid Back Non-Suspension Passenger Seat or equivalent	<input type="checkbox"/>	<input type="checkbox"/>	_____
Adjustable Steering Column	<input type="checkbox"/>	<input type="checkbox"/>	_____

INSTRUMENT PANELS & CONTROLS

Low Air Pressure Light & Buzzer	<input type="checkbox"/>	<input type="checkbox"/>	_____
Primary & Secondary Air Pressure Gauges	<input type="checkbox"/>	<input type="checkbox"/>	_____
Intake Mounted Air Restriction Indicator without Graduations	<input type="checkbox"/>	<input type="checkbox"/>	_____
ODO/Trip/Hour/Diagnostic/Voltage Display	<input type="checkbox"/>	<input type="checkbox"/>	_____
Electric Fuel Gauge	<input type="checkbox"/>	<input type="checkbox"/>	_____
Electrical Engine Coolant Temp Gauge	<input type="checkbox"/>	<input type="checkbox"/>	_____
Engine and Trip Hour Meters Integral within Driver Display	<input type="checkbox"/>	<input type="checkbox"/>	_____
Electric Engine Oil Pressure Gauge	<input type="checkbox"/>	<input type="checkbox"/>	_____
Multi-Band AM/FM	<input type="checkbox"/>	<input type="checkbox"/>	_____
Electronic MPH Speedometer with Secondary KPH Scale, with Odometer	<input type="checkbox"/>	<input type="checkbox"/>	_____
Electronic Tachometer 3000 RPM	<input type="checkbox"/>	<input type="checkbox"/>	_____
Digital Voltage Display Integral with Driver Display	<input type="checkbox"/>	<input type="checkbox"/>	_____
One Valve Parking Brake System with Warning Indicator	<input type="checkbox"/>	<input type="checkbox"/>	_____

PAINT

Cab: Imron White N0006HN	<input type="checkbox"/>	<input type="checkbox"/>	_____
--------------------------	--------------------------	--------------------------	-------

BID FORM
ROLL-OFF CONTAINER TRUCK WITH HOIST

Santa Rosa County Procurement Department
6495 Caroline Street, Suite G
Milton, Florida 32570

Date: _____

Dear Sir:

The undersigned agrees to furnish the equipment as requested by you for Santa Rosa County in your invitation to bid and certifies that the equipment bid meets or exceeds the specifications called for, except as set out in "Exceptions to Bid Conditions" and attached to this form.

Make and Model of Equipment _____

Name & Address of Bidder: _____

Cash Bid Price FOB Milton:

ROLL-OFF CONTAINER TRUCK WITH HOIST \$ _____

Delivery Date Must Be Specified _____

Company Representative Signature

Telephone

NOTE: Please return this bid form to the above address. NO OTHER BID FORM WILL BE ACCEPTED.

COMMENTS: _____

THIS FORM MUST BE SIGNED IN THE PRESENCE OF A NOTARY PUBLIC OR OTHER OFFICER AUTHORIZED TO ADMINISTER OATHS.

1. This sworn statement is submitted to _____
by _____
(print individual's name and title)
for _____
(print name of entity submitting sworn statement)

whose business address is _____
and (if applicable) its Federal Employer Identification Number (FEIN) is _____.
If the entity has no FEIN, include the Social Security Number of the individual signing this Sworn Statement: _____.

2. I understand that a "public entity crime" as defined in Paragraph 287.133(1)(g), Florida Statutes, means a violation of any state or federal law by a person with respect to and directly related to the transaction of business with any public entity or with an agency or political subdivision of any other state or with the United States, including, but not limited to, any bid or contract for goods or services to be provided to any public entity or an agency or political subdivision of any other state or of the United States and involving antitrust, fraud, theft, bribery, collusion, racketeering, conspiracy, or material misrepresentation.
3. I understand that "convicted" or "conviction" as defined in Paragraph 287.133(1)(b), Florida Statutes, means a finding of guilt or a conviction of a public entity crime, with or without an adjudication of guilt, in any federal or state trial court of record relating to charges brought by indictment or information after July 1, 1989, as a result of a jury verdict, nonjury trial, or entry of a plea of guilty or nolo contendere.
4. I understand that an "affiliate" as defined in Paragraph 287.133(1)(a), Florida Statutes, means:
 1. A predecessor or successor of a person convicted of a public entity crime; or
 2. An entity under the control of any natural person who is active in the management of the entity and who has been convicted of a public entity crime. The term "affiliate" includes those officers, directors, executives, partners, shareholders, employees, members, and agents who are active in the management of an affiliate. The ownership by one person of shares constituting a controlling interest in another person, or a pooling of equipment or income among persons when not for fair market value under an arm's length agreement, shall be a prima facie case that one person controls another person. A person who knowingly enters into a joint venture with a person who has been convicted of public entity crime.
5. I understand that a "person" as defined in Paragraph 287.133(1)(e), Florida Statutes, means any natural person or entity organized under the laws of any state or of the United States with legal power to enter into a binding contract and which bids or appeals to bid on contracts for the provision of goods and services let by a public entity, or which otherwise transacts or applies to transact business with a public entity. The term "person" includes those officers, directors, executives, partners, shareholders, employees, members, and agents who are active in management of an entity.
6. Based on information and belief, the statement which I have marked below is true in relation to the entity submitting this sworn statement. (Indicate which statement applies.)
 _____ Neither the entity submitting this sworn statement, nor one or more of the officers, directors, executives, partners, shareholders, employees, members, or agents who are active in management of the entity, nor any affiliate of the entity have been charged with and convicted of a public entity crime subsequent to July 1, 1989.
 _____ The entity submitting this sworn statement, or one or more of the officers, directors, executives, partners, shareholders, employees, members, or agents who are active in management of the entity, or an affiliate of the entity has been charged with and convicted of a public entity crime subsequent to July 1, 1989.
 _____ The entity submitting this sworn statement, or one or more of the officers, directors, executives, partners, shareholders, employees, members, or agents who are active in management of the entity, or an affiliate of the entity has been charged with and convicted of a public entity crime subsequent to July 1, 1989. However, there has been a subsequent proceeding before a Hearing Officer of the State of Florida, Division of Administrative Hearings and the Final Order entered by the Hearing Officers determined that it was not in the public interest to place the entity submitting this sworn statement on the convicted vendor list. (ATTACH A COPY OF THE FINAL ORDER.)

I UNDERSTAND THAT THE SUBMISSION OF THIS FORM TO THE CONTRACTING OFFICER FOR THE PUBLIC ENTITY IDENTIFIED IN PARAGRAPH 1 (ONE) ABOVE IS FOR THAT PUBLIC ENTITY ONLY AND THAT THIS FORM IS VALID THROUGH DECEMBER 31 OF THE CALENDAR YEAR IN WHICH IT IS FILED. I ALSO UNDERSTAND THAT I AM REQUIRED TO INFORM THE PUBLIC ENTITY PRIOR TO ENTERING INTO A CONTRACT IN EXCESS OF THE THRESHOLD AMOUNT PROVIDED IN SECTION 287.017, FLORIDA STATUTES FOR CATEGORY TWO OF ANY CHANGE IN THE INFORMATION CONTAINED IN THIS FORM.

(Signature) _____

Sworn to and subscribed before me this _____ day of _____, 2_____.

Personally known _____

or Produced identification _____ Notary Public – State of _____

(Type of identification) _____ My commission expires _____

_____ (Printed, typed, or stamped commissioned name of notary public.)